

# THE EXTEC LABCUT® 150 VARIABLE SPEED PRECISION DIAMOND SAW



A modern styled laboratory instrument designed for precision cutting of a wide variety of materials with minimal damage and deformation.

## ADVANCED FEATURES:

- Variable wheel rotation speed range from 0 to 1000 RPM
- Operated by utilizing the EZ-DRO™ Keypad
- Pivoted Specimen Arm with 25mm Micrometer Movement
- Transparent Polycarbonate Splash/Safety Shield
- Recirculating Coolant System consists of a coolant reservoir with an adjustable power supply, liquid recirculation pump, and twin coolant tubes

## SPECIFICATIONS:

- Accepts 3 inch (75mm) , 4 inch (100mm), 5 inch (125mm) and 6 inch (150 mm) Diamond Wafering Blades and Abrasive Wheels
- Powerful Belt Driven AC ¼ HP (0.18kW) motor with inverter
- Micrometer: 0-25 mm (>1 inch) 0.01mm (< .0040 inch)
- Variable wheel speed: 0-1000 RPM
- Available in 110v and 220v
- L 16" x W 12" x H 8" (Main Body Height); 40 lb

# THE EXTEC LABCUT® 150 VARIABLE SPEED PRECISION DIAMOND SAW

The EXTEC Labcut® 150 Variable Speed Precision Diamond Saw is an attractive, modern styled laboratory instrument designed for precision cutting of a wide variety of materials. Samples can be cut with minimal damage and deformation. The universal design and variable speed aid the precision cutting of fragile and soft materials. Variable wheel rotation speeds range from 0 to 1000 rpm. A variety of sample holders add to the 150's versatility.

The Labcut® 150 is ruggedly constructed from a cast-aluminum frame with stainless steel components providing stability and corrosion resistance in a molded water resistant cabinet. The EZ-DRO™ Easy Keypad operates the powerful belt driven AC 1/4 HP motor with inverter. The sample arm is pivoted and can be counterbalanced to provide low loading conditions on the specimen. It features 25mm micrometer movement that allows positioning of the sample with respect to the wheel.

The Recirculating Coolant System consists of a coolant reservoir with an adjustable power supply, liquid recirculation pump, twin coolant tubes, stainless perforated tray, sample retrieval tweezers and sump drain tool. The system provides adequate coolant flow to the twin coolant tubes located on either side of the cutting wheel. The Recirculating Coolant System accepts EXTEC cutting fluids.

The Labcut® 150 accepts 3 inch (75mm), 4 inch (100mm), 5 inch (125mm) and 6 inch (150mm) diameter diamond wafering blades and abrasive cut-off wheels. A transparent polycarbonate splash/safety shield with an integrated safety switch is fitted to prevent operation when the shield is open. An endpoint microswitch indicator can be set to terminate the cutting process at a predetermined depth.

CATALOG NUMBER	DESCRIPTION
10150	Exttec Labcut® Model 150 Variable Speed, 3" - 6", Includes: 10015 Screw Holder For Irregular Samples, Set Of 3 Weights, Tools And Digital Rpm Indicator, 10153 Splash Guard, And 12050 Cutting Fluid (110v)
10150-220	Exttec Labcut® Model 150 Variable Speed, 3" - 6", Includes: 10015 Screw Holder For Irregular Samples, Set Of 3 Weights, Tools And Digital Rpm Indicator, 10153 Splash Guard, And 12050 Cutting Fluid (220v)

CATALOG NUMBER	ACCESSORIES
10015	Exttec Screw Holder F/Irregular Samples (one included with unit)
10020	Exttec V-Block Holder Small
10022	Exttec V-Block Holder Large
10024	Exttec Double Clamp Holder
10027	Exttec ½ - 2" (12 mm to 50 mm) Cylindrical Holder
10028	Exttec Ceramic Disc Holder with 3 Discs
10030	Exttec Mounting Plate 38 mm x 25 mm
10031	Exttec Mounting Plate 38 mm
10032	Exttec Mounting Plate 25 mm
10034	Exttec Mounting Stubs 19 mm (pkg/5)
10035	Exttec PCB Holder
10047	Exttec Vacuum Chuck Complete with Pump
1125-10150-00	Exttec Shipping Crate